

-SUBSTITUTE SPECIFICATION-

Docket #72130

MACHINE AND METHOD FOR PRODUCING CARDBOARD TUBES

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a United States National Phase application of International Application PCT/IT2005/000046 and claims the benefit of priority under 35 U.S.C. § 119 of Italian application FI2004A000046 filed 24/Feb./2004, the entire contents of which are
5 incorporated herein by reference.

FIELD OF THE INVENTION

[0002] The present invention pertains to a machine and a method for producing cardboard tubes.

BACKGROUND OF THE INVENTION

10 **[0003]** It is known that a machine for producing cardboard tubes basically comprises:

[0004] - means for continuously feeding two or more ribbons made of paper or similar material, at least one ribbon being provided with a predetermined amount of glue in correspondence of one of its sides, the ribbons being drawn from corresponding bobbins which are supported by the feeding means;

5 **[0005]** - belt type means, which are positioned downstream of the feeding means, for winding and advancing the ribbons onto a spindle, forming a plurality of spirals which are overlapped and staggered according to a predetermined staggering step, so that the tube results from the reciprocal overlapping and gluing of the ribbons which are spirally wound on the spindle;

[0006] - means, which are positioned downstream of the spindle, for cutting the
10 continuous tube into elements having a predetermined length.

[0007] The first ribbon, I. e. the ribbon destined to directly contact the spindle, is not glued, to avoid its adhesion to the spindle surface.

[0008] In practice, the belt means, which are positioned onto the spindle downstream of with respect to the feeding direction of the ribbons, drawn the ribbons by exerting on them a
15 traction force which is directed towards the spindle and, while it is forming, the tube made by the overlapped spiral ribbons advances and rotates about the longitudinal axis of the spindle.

[0009] The intervention rate of the cutting means depends on the advancing speed of the

tube onto the spindle and on the predetermined length of the elements obtained from the tube.

[0010] Such a machine is described in WO 95/10400 and WO 95/10399.

[0011] One of the main drawbacks deriving from of such machines lies in a cleavage of the tube in correspondence of the cut sections. This drawback is even more evident when the operative speed of the machine increases.

SUMMARY OF THE INVENTION

[0012] The main aim of the present invention is to eliminate this drawback.

[0013] This result has been achieved, according to the invention, by a method for producing cardboard tubes by winding a plurality of ribbons onto a spindle, where a preset number of the ribbons are glued in correspondence of the lower surface thereof. A predetermined amount of supplementary quick setting glue is applied on the lower surface of the last ribbon destined to be wound on the spindle. This supplementary glue is arranged in proximity to at least a longitudinal edge of the ribbon forming a corresponding stripe of quick setting glue astride or adjacent a section (ST) of the ribbon. This section (ST) is arranged to be acted on by a subsequent cutting action executed downstream of the spindle. The application of the at least one stripe of supplementary glue is operated at intervals corresponding to a preset length of the last ribbon.

[0014] The present invention also relates to a cardboard tube producing machine, with a structure supporting feeding means for a plurality of ribbons of paper or paper-like material, and a spindle. The ribbons are wound on the spindle. The ribbons are glued in correspondence of the respective lower surfaces, with the exception of the first ribbon which is destined to the direct contact with the spindle. Means are provided for moving the ribbons and winding them on the spindle. The machine also comprises supplementary glue means disposed and acting along a path of the ribbon, the upper surface of which is destined to define the outer surface of a tube. The supplementary glue means distributes a stripe of supplementary quick setting glue in proximity to almost a longitudinal edge of the lower surface of the ribbon astride of a section of the latter interested by a subsequent cutting operation downstream of the spindle. The supplementary glue means being operated at intervals corresponding to a present length of the last ribbon.

[0015] Thanks to the present invention, it is possible to increase the operative speed of the machine, i.e. the feeding speed of the ribbons and, consequently, the tubes producing speed, without the aforesaid cleavage effect.

[0016] Furthermore, a machine according to the present invention is relatively simple to make, cost-effective and reliable even after a prolonged service life and it may also be realized by modifying the existing machines, without adversely affecting the functionality thereof, at a cost which is very low when compared with the advantages which are obtained.

[0017] The various features of novelty which characterize the invention are pointed out

with particularity in the claims annexed to and forming a part of this disclosure. For a better understanding of the invention, its operating advantages and specific objects attained by its uses, reference is made to the accompanying drawings and descriptive matter in which preferred embodiments of the invention are illustrated.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

[0018] Fig. 1 is a partial perspective view of a machine according to the present invention;

[0019] Fig. 2 is a view of a particular area, represented in perspective view from the bottom, relating to the injectors for the application of the glue on the lower surface of the second ribbon treated in the machine of Fig. 1;

[0020] Fig. 3 is a schematic view of the lower surface of a portion of the second ribbon treated in the machine of Fig. 1, in which, in particular, is shown the relative position of two gluing lines;

[0021] Fig. 4 is a schematic plan view of a tube portion obtained by the spiral winding of two ribbons of the same width, in which, in particular, are shown the two gluing lines of Fig. 3;

[0022] Fig. 5 is a schematic plan view of two ribbons of different width at the entrance of the section of the machine comprising the spindle: in the figure is shown a gluing line applied on

the lower surface of the wider upper ribbon, even if this line is on the other face of the sheet;

[0023] Fig. 6 is a schematic plan view of a tube portion obtained by the winding of the two ribbons of Fig. 5;

[0024] Fig. 7 is a simplified block diagram of the control system driving the means for
5 applying a supplementary amount of quick setting glue;

[0025] Fig. 8 is a schematic representation relating to the cleavage of a conventional cardboard tube in correspondence of an end section;

[0026] Fig. 9 is a representation similar to that of Fig. 8 but referred to a cardboard tube obtained according to the present invention.

10 DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0027] Referring to the drawings in particular, a machine according to the present invention comprises, similarly to the conventional machines:

[0028] - a structure (S) supporting a plurality of bobbins (not shown for sake of simplicity) from which are unwound more ribbons (U, L) of paper or paper-like material;

15 **[0029]** - a plurality of gluing rolls (not shown for sake of simplicity) which are disposed

downstream of the bobbins in respect to the advancing direction (X) of the ribbons (U,L) along a wall of the structure (S) and which are feed by corresponding tanks (also not shown for sake of simplicity) containing liquid glue, for applying a predetermined amount of glue on the lower surface of each of the advancing ribbons (U, L), with the exception of the first ribbon (L), I. e.

5 with the exception of the ribbon (L), the lower surface of which is destined to the direct contact with a spindle 1 disposed downstream, on which the tubes are formed;

[0030] - a spindle 1 which is longitudinally developed along the direction of the tube to be produced, the ribbons (U, L) being wound onto the spindle forming a plurality of superimposed and staggered spirals;

10 **[0031]** - belt means 2, with relevant motor means 20, for spirally winding the ribbons (U, L) onto the spindle 1 and advancing the forming tube along the longitudinal axis (m-m) of the same spindle 1;

[0032] cutting means (not shown for sake of clarity) for subdividing the tube (T) into portions or tubular elements having a predetermined length.

15 **[0033]** As stated above, the feeding and gluing means acting on the ribbons (U, L), the winding means and the means for cutting the tube (which results from the overlapping and reciprocal gluing of the ribbons spirally wound onto the spindle) are known to those skilled in the art and, therefore, it is omitted a more detailed description thereof. The gluing of the lower

surface of the ribbons (U, L) is made, according to a known technique, upstream of the spindle 1, by means of liquid glue, the liquid glue exploiting its adhesive power in a relatively long time to avoid that it became dry along the path between the gluing station (I. e. the station where the tanks containing the liquid glue are positioned) and the spindle 1.

5 **[0034]** The machine comprises means 3 for applying a predetermined amount of supplementary glue of the quick setting type to the lower surface (I. e. the surface destined to look at the spindle 1) of at least one of the ribbons which are wound onto the spindle 1 and, more precisely, to the lower surface of the last ribbon, I. e. that ribbon the upper surface of which defines the external surface of the tube.

10 **[0035]** The means 3 are connected to a tank for the quick setting glue which, for sake of simplicity, is not shown in the enclosed drawings.

[0036] The wording "quick setting glue" denotes a glue having a high adhesive power acting in a short time.

15 **[0037]** With reference to the examples shown in the enclosed drawings, the means 3 distribute the quick setting glue on the lower surface of the second ribbon (U), which is the last ribbon and travels along a path overhanging the advancing path of the first ribbon (L), the tube being constituted by only two ribbons spirally wound and superimposed.

[0038] When the ribbons are three instead of two, the means 3 distribute the glue on the lower surface of the third ribbon, I e. always on the lower surface of the last ribbon.

[0039] According to the example shown in the drawings, the means 3 comprise a

distributor apt to distribute "hot melt" glue, whose body is solid to the structure (S), in such a

5 manner to result downstream of the gluing rolls and upstream of the spindle 1. The distributor 3

comprises a couple of injectors 30 fixed to a plate 31 solid to the structure (S) near the exit

section of the latter, with the respective nozzles 31 directed to the lower surface (UV) of the

ribbon to be treated (in the example, the lower surface of the second ribbon U). In

correspondence with the injectors 30, the ribbon (U) to be treated is kept in guide by a wing 33 of

10 the plate 31 oriented parallel to the advancing direction (X) of the ribbon and which is spaced

from the nozzles 31 of the two injectors 30 in such a manner that the ribbon (U) passes through

the space between the wing 33 and the nozzles 31, with the upper surface turned towards the

wing 33 and the lower surface (UV) turned towards the nozzles 31. The injectors 30 are disposed

and acting in such a manner to distribute a preset amount of quick setting glue (for example, a "hot

15 melt" glue) in correspondence of at least one of the longitudinal edges of the lower surface (UV)

of the ribbon (U) advancing towards the spindle 1. Preferably, the injectors 30 distribute a preset

amount of quick setting glue in proximity to both the longitudinal edges (BU) of the last ribbon

(U) if this has the same width of the underlying ribbon(L) and in correspondence of only one edge

(BU) if the upper ribbon (U) has a greater width than the lower ribbon (L). Obviously, also in the

20 second case it is possible to distribute quick setting glue on both the longitudinal edges of the

upper ribbon or last ribbon (U).

[0040] Referring to the first of the two examples, I. e. when the two ribbons (U) and (L) have the same width, the injectors 30 are activated, for a preset time, in such a manner to apply two stripes of quick setting glue (G) on the lower surface (UV) of the last ribbon (U) astride of a section (ST) subsequently involved by the action of the cutting means acting downstream of the spindle 1. The section (ST) is, as more clearly shown in Fig. 3, inclined of a preset angle δ in respect to the longitudinal axis (u-u) of the ribbon (U). The angle (δ) is the complementary of the angle formed by the plan projection of the longitudinal axis of each ribbon (L, U) with the longitudinal axis (m-m) of the spindle 1 when the ribbons are wound on the latter (see Fig. 4); furthermore, this angle corresponds to the angle formed by each stripe of quick setting glue (G) with the section (ST).

[0041] As shown in Fig. 4, when the tube formed by the spirals of the ribbons (U, L) wound on the spindle 1 is cut, since the cut is operated in correspondence of the section interested or arranged by the stripes of quick setting glue (G), both the stripes (G) are cut and a portion of each of them is both upstream and downstream of the cutting section.

[0042] Therefore, when the cut is executed, both upstream and downstream of the section (ST) the corresponding edges of the ribbons (U, L) are strongly anchored to each other. In this way, it is avoided the cleavage phenomenon characteristic of the tubes produced by the conventional machines, schematically represented in Fig. 8, where "SF" denotes an edge of the last ribbon detached from the underlying ribbon in correspondence of an end section of the tube, I. e. in correspondence of the section interested or arranged by the cut. On the contrary, as shown in

Fig. 9. a tube (T) according to the present invention is exempt from such phenomenon.

[0043] Referring to the second example, since the last ribbon (U), i.e. the ribbon whose upper surface defines the outer surface of the tube (T), is wider than the underlying ribbon (L), it can be sufficient to distribute a preset amount of supplementary quick setting glue in
5 correspondence of only one of its longitudinal edges (BU).

[0044] In the scheme or embodiment of Fig. 5, the glue stripe (G) is represented with continuous line, even if it is on the opposite face of the sheet and it is in proximity to the right edge (BU) of the ribbon (U). In the scheme of Fig. 6, the discontinuous lines marked by the reference (BL) correspond to the coinciding edges of the lower ribbon (L), spirally wound on the
10 spindle 1 and the glue stripe (G) is represented with continuous line, even if it is on the lower surface of the last ribbon (U), for a better highlight of the same.

[0045] When only one supplementary glue stripe (G) is to be applied, then it is activated only the corresponding injector 30 instead of both the injectors.

[0046] Therefore the two injectors 30 are placed in such a way to have the respective
15 nozzle 31 disposed on the plane defined by the section (ST) and are activated at the same time for applying two stripes of quick setting glue (G) astride of the section (ST).

[0047] The distance between the nozzles 31 of the two injectors 30 depends on the width

(LA) of the ribbon (U).

[0048] The activation of the injectors 30 is operated on the basis of the length of the completed tubes to be produced, I. e. in function of the length of the tubes obtained from the cutting of the ribbons wound and glued spirally on the spindle 1. For example, calling "LA" the width of the ribbon (U), "D" the diameter of the spindle and "LT" the length of the tube to be produced, the injectors 30 are activated for a preset time when in correspondence of them passes a portion of ribbon (U) of length equal to $LT \cdot D \cdot n / LA$. The activation time of the injectors is preset on the basis of the desired length of each stripe of supplementary quick setting glue (G).

[0049] The control of the amount of ribbon (U) which advances in front of the nozzles 31 of the injectors 30 can be operated by means of an encoder (4) mounted on the axis of an idly roll having a surface covered by friction material; the ribbon passes on this surface, around the roll and determines the rotation of the same roll. This control system, disposed upstream of the means 3, is well known in the technical field. The encoder 4 is connected with a programmable electronic unit 5 apt to receive the data from the encoder 4 for processing them on the basis of the formula previously indicated and apt to operate the activation of the injectors 30 when the preset length value is reached. The structure and the working of the electronic control means are known by the technicians of the industrial automation and, therefore, aren't described in detail.

[0050] According to present invention, an operational method involves to apply, in addition to the glue normally used for obtaining the reciprocal attachment of the two ribbons (U,

L) spirally wound, a preset amount of supplementary quick setting glue (for example, a "hot melt" glue) in correspondence of the interface between the penultimate ribbon and the last one, astride of a section (ST) subsequently interested by the action of the cutting means downstream of the spindle 1.

5 **[0051]** Practically, all the construction details may vary in any equivalent way as far as the shape, dimensions, elements disposition, nature of the used materials are concerned, without nevertheless departing from the scope of the adopted solution idea and, thereby, remaining within the limits of the protection granted to the present patent for invention.

10 **[0052]** While specific embodiments of the invention have been shown and described in detail to illustrate the application of the principles of the invention, it will be understood that the invention may be embodied otherwise without departing from such principles.